

Product data sheet

SIDISTAR® T100

Elkem ASA Silicon Products
 Drammensveien 169 P.O. Box 334
 Skøyen NO-0213 OSLO
 www.elkem.com

Description SIDISTAR® T100 is a specially designed grey-coloured process modifier consisting of spherical, sub-micron, particles of silicon dioxide. The nature of the product allows excellent dispersion of these particles in the polymer matrix. This leads to improved distribution of all compound ingredients and a better flow, allowing higher extrusion speeds and smoother surface of the end product. The product is supplied in a densified, free flowing, form.

Applications SIDISTAR® T100 has been designed for usage in thermoplastics. Areas of use include flame retardant cable compounds, and improved fibre dispersion in thermoplastics. The densified version is specifically designed for easier handling in higher viscosity polymer systems where a medium amount of shear energy is needed for full dispersion.

Chemical analysis & physical data

Properties	Test Method	Unit	Limits
SiO ₂ (<i>Silicon dioxide, amorphous</i>)	ESM-LAB-18	%	96.0 - 99.0
C (<i>Carbon</i>)	ESM-LAB-05	%	≤ 1.50
Fe ₂ O ₃ (<i>Iron oxide</i>)	ESM-LAB-17	%	≤ 0.25
H ₂ O (<i>Moisture, when packed</i>)	ESM-LAB-02	%	≤ 0.8
Loss on Ignition (L.O.I.) @ 950 °C	ESM-LAB-03	%	≤ 1.80
pH-value (<i>fresh</i>)	ESM-LAB-10		6.5 - 8.5
Bulk Density (<i>when packed</i>)	ESM-LAB-08	kg/m ³	400 - 700
Properties (<i>measured on undensified material</i>)	Test Method	Unit	Typical Values**
Specific surface area (<i>BET</i>)		m ² /g	20 - 30
Median particle size		µm	0.15
Specific Gravity		g/cm ³	2.2

** Typical values are for indicational use only, values are not part of Elkem Silicon Materials standard analysis.

Product data sheet

SIDISTAR® T100

Elkem ASA Silicon Products
 Drammensveien 169 P.O. Box 334
 Skøyen NO-0213 OSLO
www.elkem.com

Packaging

	1 big bag	50 small bags
Bags on pallet	1 big bag	50 small bags
Bag material	Coated woven polypropylene fabric	LDPE bag
Cover / protection	LDPE shrink hood	LDPE shrink hood
Pallet	Fumigated wood	Fumigated wood

Dimensions (metric)

Net weight 1 bag	850 kg	20 kg
Net weight on pallet	850 kg	1000 kg
Gross weight	870 kg	1020 kg
Bag dimensions (L x W x H)	106 x 106 x 142 cm	73 x 46 x 20 cm
Discharge spout	Ø: 42 cm, Length 70 cm	
Pallet dimensions incl bags (L x W x H)	105 x 105 x 143 cm	120 x 100 x 140 cm

Dimensions (imperial)

Net weight 1 bag	1874 lb	44 lb
Net weight on pallet	1874 lb	2205 lb
Gross weight	1918 lb	2249 lb
Bag dimensions (L x W x H)	41.7 x 41.7 x 55.9 in	28.7 x 18.1 x 7.9 in
Discharge spout	Ø: 16.5 in, Length 27.6 in	
Pallet dimensions incl bags (L x W x H)	41.3 x 41.3 x 56.3 in	47.2 x 39.4 x 55.1 in

Storage and handling The product is recommended to be stored in a covered dry place, protected from direct UV light. Recommended storage temperature between +5 °C and +40 °C (+45 °F and +104 °F). It's important that the minimum temperature is > 5 °C (9 °F) above the dew point. Recommended relative humidity < 85 %.

Shelf life We recommend that the product should be used within 2 years from production date

Health, safety & environment The product safety information, as well as REACH information, can be found on our website: www.sidistar.com.

Quality assurance Elkem's management system is certified to ISO 9001:2015.

Sustainability For Elkem, sustainability is central to our business strategy. Our mission is to provide advanced material solutions shaping a better and more sustainable future, adding value to our stakeholders globally. We are committed to reducing in embodied carbon emission. For further information, please visit www.elkem.com/sustainability/ or contact us to learn more about our sustainability roadmap.

Additional information and contact For further information about SIDISTAR®, a contact list can be found on our webpage www.sidistar.com